

# Product data sheet

Specifications

SQUARE D



Mini circuit breaker, Homeline, 15A, 1 pole, 120/240VAC, 10kA AIR, standard type, plug in, UL

HOM115

Product availability: Stock - Normally stocked in distribution facility

## Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	15 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	1P
Short Circuit Current Rating	10 kA
Number of Spaces	1
Circuit Breaker Type	Standard
Ratings	HACR and Switching Duty rated
Electrical Connection	Clamp terminal for 2 cables
Wire Size	1 x AWG 14...AWG 8 ( aluminium/copper ) 2 x AWG 14...AWG 10 ( copper )

## Complementary

Tightening torque	35.4 lbf.in (4.0 N.m) 0.004...0.009 in <sup>2</sup> (2.5...6 mm <sup>2</sup> ) (AWG 14...AWG 8)
Height	3.13 in (79.50 mm)
Width	1 in (25.4 mm)
Depth	2.98 in (75.69 mm)

## Environment

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

## Ordering and shipping details

Category	US1DE3D00046
Discount Schedule	DE3D
GTIN	785901065203
Returnability	Yes
Country of origin	US

## Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	1.00 in (2.54 cm)
<b>Package 1 Width</b>	3.00 in (7.62 cm)
<b>Package 1 Length</b>	3.00 in (7.62 cm)
<b>Package 1 Weight</b>	4.656 oz (131.995 g)
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	3.60 in (9.144 cm)
<b>Package 2 Width</b>	3.00 in (7.62 cm)
<b>Package 2 Length</b>	11.10 in (28.194 cm)
<b>Package 2 Weight</b>	2.840 lb(US) (1.288 kg)
<b>Unit Type of Package 3</b>	CAR
<b>Number of Units in Package 3</b>	100
<b>Package 3 Height</b>	11.10 in (28.194 cm)
<b>Package 3 Width</b>	7.10 in (18.034 cm)
<b>Package 3 Length</b>	16.70 in (42.418 cm)
<b>Package 3 Weight</b>	29.150 lb(US) (13.222 kg)

## Contractual warranty

<b>Warranty</b>	Lifetime
-----------------	----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 22

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No



Image of product / Alternate images

Alternative

Technical Benefits  
Thermal Magnetic Breaker



Miniature circuit breaker rated at 15A



Protects against overloads and short-circuits



For residential/commercial use to protect entire branch circuits



The current capacity that this circuit breaker is able to interrupt before breaking is 10kA



Commercially package and ready to be sold



Compatible with Homeline electrical panels and CSEDs with 1 spaces



**Homeline™**  
**HOM115**  
**15 A**  
120/240 VAC ~ 50/60Hz  
10,000 AIR/A nom.I

 **1 Pole**  
**Polo**

 **Plug-On**  
**Enchufable**







### Compatible products

Homeline 15 Amp Single Pole Circuit Breaker  
MFG Model Number: HOM115CP

→

Compatible with Homeline electrical panels and CSEDs with 1 space

HOM1HTCP

HOM1PACP

...