

# ZS-SPGV-50 Globe Valve Weathershield

For Use with Belimo Rotary Actuators



| Technical Data            |                                         |
|---------------------------|-----------------------------------------|
| Gasket                    | Rubberized PVC                          |
| Hardware                  | Brass inserts and screws                |
| Frame, plate, base        | PVC                                     |
| Housing Material          | Grey Rigid Molded PVC                   |
| Ambient Temperature Range | -22°F to 122°F [-30°C to +50°C]         |
| Humidity                  | 5 to 95% RH non-condensing              |
| Housing                   | Designed to Nema 4 standards less holes |
| Weight                    | 7.3 LB [3.3 kg]                         |

## Application


The ZS-SPGV series weather shields provide moderate protection to globe valve actuators which are mounted outdoors. This product is not designed as a water tight enclosure due to the added holes for mounting. The one piece PVC housing allows for easy mounting of standard rotary style actuators.

## Operation

The ZS-SPGV series weather shields are supplied as a one piece PVC enclosure with a removable cover. Holes can be added in the field to allow for connection of conduit connectors to the housing. There are removable screws to open the cover to mount and access the actuators. Also supplied is a rubberized gasket to ensure a tight seal.

## Suitable Actuators

|            | Non-Spring | Electronic Fail-Safe |
|------------|------------|----------------------|
| ZS-SPGV-50 | 2*GMB(X)   | 2*GKB(X)             |



| A            | C            | D          |
|--------------|--------------|------------|
| 12.88" [327] | 12.88" [327] | 4.6" [117] |